


Pro-Series Gas Drivers FONDA

















		7				
						UI UI
Applications	Ranch Pro [™]	Fence Pro [™]	Multi-Pro [™]	Multi-Pro XA [™]	Multi-Pro TS™	Multi-Pro CP™
Chuck Size (mm)	1¾" ID (44.4)	2½" ID (63.5)	2½" ID (63.5)	2½" ID (63.5)	2¾" ID (69.85)	2½" ID (63.5)
Weight (kg)	33 lbs (15)	38 lbs (17.24)	44 lbs (19.9)	54.5 lbs (24.72)	51 lbs (23.13)	47.25 (27.3)
Power						
Performance						
T-Post	✓	✓•	✓	✓		
Ground Rod	✓	✓•	✓	✓		
Form Pin	✓	✓•	✓	✓		
1—1-5/8" Dia.	✓	✓•	✓	✓		
1-3/4—2-3/8" Dia		✓	✓	✓		
Tent Stake			✓•		✓	
1-1/2—2-1/2" Square Tube			✓•	✓•		✓•
1.2—4 lb Channel				✓•		✓
Silt Fence				✓•		✓
2-1/2—3-7/8 Round Solid Wood Post				✓•		✓•
2—2-7/8 Square Solid Wood Post				✓•		å

Accessories





Rhino® Rental Pro Kit includes:

Rhino® GPD Transport Cart®, Multi-Pro XA[™] Post Driver, Short chuck with 2 drive caps for break away sign anchors, **Slotted Chuck for Channel Posts** part no. 301951



Rhino® Pro-Series Top Throttle



Add to any Pro-Series Post Driver with tube-style handles. Drive posts low to the ground with less bending, and easier manuverability for repetitive post driving. Part no. 301600

isit rhinotool.com for our full line of accessories

Air Operated Post Drivers

Order a Rhino® **Throttle Valve Kit** and FRL (filter-regulator-lubricator) to extend the life of your pneumatic post driver.













		inning (E I	T T		
Applications	PD-45™	PD-55™	PD-110™	PD-140™	PD-200™	PD-200™
Chuck Size (mm)	3" ID (76.2)	3-7/8" ID (98.4)	4-1/4" ID (107.9)	4-1/4" ID (107.9)	5-1/2" ID (139.7)	7" ID (177.8)
Weight (kg)	46.3 lbs (21)	54.6 lbs (24.8)	109.16 lbs (49.5)	138.4 lbs (62.8)	170 lbs (77.11)	177 (80.28)
Air Consumption (CFM@90 psi)	30	42	64	64	72	72
Duty	Light	Medium	Heavy	Heavy Duty	Heavy Duty	Heavy Duty
Fiberglass T-Post	✓•	✓•	✓•	✓•		
T-Post	✓•	✓•	✓•	✓•		
3/4"—1" Ground Rod	✓	✓				
3/4"—1-1/2" Reinforcing Tent Bar Stake	✓	✓				
1" Concrete Form Pin	✓	✓				
1" Pipe O.D.	✓	✓				
1-1/4—1-1/2" Pipe O.D.	å	✓•	✓•	✓•		
1-5/8" Round Post O.D.	✓•	✓•	✓•	✓•		
2" Pipe O.D.	å	å	å	✓•	✓•	✓•
2-1/2" Pipe O.D.	√ ♦	√• * •	å	å	✓•	å
3" Pipe O.D.		√• ∻♦	√• * ♦	√• * ♦	√• * •	√• * ♦
3 1/2" Pipe O.D.			√ +	√ +	√• * ♦	√• *•
4" Pipe O.D.			√■÷♦	√■÷♦	√• * ♦	å
5" to 6" Pipe O.D.						å * +
1.2 to 1.5 lbs/ft Channel Posts	å	å	✓•	✓•		
2 to 2.75 lbs/ft Channel Posts		å	✓•	å		
3 to 4 lbs/ft Channel Posts		å	✓•	✓•		
Rectangular Posts	✓	✓				
Telespar Posts		å	å	å	å	✓•
Telespar Post Breakaway Anchor 2-1/4"		√• * ♦	√• *•	√• *•	å	
Telespar Post Breakaway Anchor 2-1/2"		√• ÷ •	√• ÷ •	√• ÷ •	å	
Channel Post Breakaway Anchor		√• *•	√• *•	√• * ♦	√• *•	
C Posts		✓	✓	✓	✓•	å
Super C Post				✓	å	å
4" x 4" Wood Post		✓■	✓■	✓■	✓=	✓■
4" x 6" H Column Guardrail Post			√ ■ ⊹ ♦	√ ■ ⊹ ♦	√≡÷♦	√≡÷♦
6" x 6" Wood Points					✓■	✓■
Well Points (Sand Points)				å	å	å
12" Sheet Piling				✓■	✓■	√ ■

■An optional master chuck is required ●An adapter is required ♦A driving cap is required ❖ Indicates a combination of accessories is required

^{* *} May increase or decrease depending on material being driven