

Multi-Pro™

Multi-Pro Gas Post Driver



Pneumatic • Hydraulic • Gasoline
Professional Grade Tools

Adaptable to fit your post installation challenges

The Rhino® Multi-Pro™ Gas Post Driver powered by a Honda 4-cycle engine, is engineered with increased driving dynamics to drive larger posts and the versatility to take on more post driving applications.

- Larger body, hammer, and anvil provide 35% more hitting power than the Fence Pro™
- Includes Rhino® Chuck-Lok™ 1", 1 - 3/4", 2" Adapters
- Versatile external chuck design can be configured for driving 1.2-4 lb channel post, tent stake, or 1-3/4" to 2-1/2" square sign post and square post sign anchor with a drive cap.
- Quick change chuck is designed to receive the Chuck-Lok™ Adapter System and be quickly removed when changing accessories
- Two-piece adapter design allows quick removal of driver from the post
- Equipped with Rhino's CIS™ Vibration Dampening
- Padded grip for handling comfort
- Powered by Honda® GX35 4-Stroke Engine
- Shock resistant heat-treated steel components
- Double sided, sealed bearings on all rotating parts
- Removable bottom handle



See it in action!



Use your phone to scan the QR code to view a Multi-Pro Video on YouTube



Applications	
Types & Sizes of Posts to be Driven O.D.(outside dimensions)	Chuck/Adapter
T-Post	1-3/4" Adapter (Included)
Ground Rod, 1/2" & 3/4"	1" Adapter (Included)
Concrete Form Pin, 1"	1" Adapter (Included)
Round Pipe, 1" to 1-5/8"	1-3/4" Adapter (Included)
Round Pipe, 1-7/8"	2" Adapter (Included)
Round Pipe, 1-3/4" to 2-3/8"	Standard Chuck (Included)
Square Tube, 1-1/2" to 2-1/2"	Square Tube Chuck (Optional) *

*Drive Cap Option is also required for this application

Specifications	
Master Chuck ID	2.5" (63.5 mm)
Driver Only Dimensions	11" W x 14" D x 26.75" H (280 x 356 x 680 mm)
Driver Only Weight	43.7 lbs. (19.8 kg)
Engine	Honda GX35 4-Stroke
BPM (beats per minute)	1720 (approximate)
Fuel	Unleaded Gas, 86 Octane or Higher
Fuel Capacity	0.67 qt. (0.63 ltr)
Engine Oil	SAE 10W-30
Lubricant	RHINO® Pro Series Grease
Shipping Weight	53 lbs. (24 kg)
Shipping Dimensions	30.5" L x 15" W x 18.25" H (775 x 381 x 464 mm)

Note: Custom chucks may be available for your specific application contact Rhino Tool Company.

Part No.	Description
301002	Rhino® Multi-Pro™ Gas Driver w/Chuck Lok Syst.
300902	2" (50.8mm) Adapter (Included)
300895	1¾" (44.4mm) Adapter (Included)
300900	1" (25.4mm) Adapter (Included)
301000	¼" Long Arm Hex Key (Included)
300513	Oil, 3.2 oz. Bottle (Included)



Order Information and Accessories	
Part No.	Description
301920	Chuck-Lok™ Locking Nut
301155	Tent Stake Chuck
301425	Square Tube Chuck
300957	1¾" (44.45mm) OD Square Tube Drive Cap
300958	2" (50.8mm) OD Square Tube Drive Cap
300959	2¼" (57.15mm) OD Square Tube Drive Cap
300960	2½" (63.5mm) OD Square Tube Drive Cap
300500	Rhino® Pro Series Grease (2.75 oz)
300506	Rhino® Pro Series Grease - 12-pack
301525	Multi-Pro™ Service Kit
301250	Extended Handle Kit - 2' Long
301252	Extended Handle Kit - 4.5' Long
290050	Transport Cart
301600	Top Throttle Kit
301525	Multi-Pro™ Service Kit

A Tradition of Quality and Service Since 1975

Visit rhinotool.com/dealer to find your nearest Rhino® retailer.

© Copyright 2021 Rhino Tool Company, Inc. 000341.23.05.11

 www.rhinotool.com
 866-707-1808